

## 4-20 mA Output

GA500  
Remote  
MountGA510  
Local  
Mount

The GA500 is a remote mount 4-20 mA Output Transmitter without display. Choose the GA510 when a local mount is needed.

## GA500/GA510 – SPECIFICATIONS

Accuracy:	± 0.1% of reading
Output Options:	
Primary Output:	Loop (4-20 mA or 0-20 mA)
Minimum:	1.5 mA
Maximum:	25 mA
Auxiliary Outputs 0-5 V:	Single Ended
Minimum:	0.1 V
Maximum:	4.9 V
Pulse-Out:	
Max. "OFF" Voltage:	60 V
Max. "ON" Current:	200 mA
Max. "ON" Voltage Drop:	< 0.5 V @ 200 mA
Electrical:	
Strain Relief:	Hubble PG7
Strain Relief Thread:	Female 1/2-20 UNF-2B
Cable:	Remote: Belden 9363 (500 Series only) Local: No cable provided
Cable Length:	20 ft. (6 m) provided (500 Series only)
Power Supply:	2-wire, loop powered
Voltage Supply (Min.):	8.5 VDC
Voltage Supply (Max.):	35 VDC
Input Options:	Hall Effect, Reed Switch, Open Collector or Low Level Sine Wave
Mounting:	Pipe or wall
Operating Temperature:	+32° F to +140° F (0° C to +60° C)
Frequency Input:	
Low Level Coil (LLC):	0.25 - 1000 Hz
High Level Low Freq.:	0.25 - 150 Hz
High Level High Freq.:	0.25 - 1000 Hz
Optically Isolated HLLF:	w/2500 V optical isolation
Optically Isolated HLHF:	w/2500 V optical isolation
Enclosure Rating:	NEMA 4X / IP55
Shipping Weight:	Remote: 2.0 lbs. (.90 kg) Local: 1.1 lbs. (.5 kg)

## APPROVALS



## ACCURACY: ±0.1% READING

## Features and Benefits:

- ✓ Provides communication with process control equipment.
- ✓ Works with G Series, G2 Turbine Meters and GM Oval Gear Meters.
- ✓ Now available with Lockout feature.
- ✓ Microprocessor-based electronics have extremely low power requirements.
- ✓ Easy to set 4-20 mA endpoints under actual flow conditions.
- ✓ A signal conditioner with industry standard current loop output.
- ✓ Easily mounted on pipe or wall.